

NSB 100FT BLUE+



The NSB BLUE+ Battery® delivers ultra fast recharge and exceptional PSoC cycling performance.

- Exceptional PSoC cyclic performance 2050 cycles @50% DoD
- Design life 12+ years at 20°C (68°F)
- EUROBAT design life definition: Very Long Life (12+ years)
- Ultra fast recharge
- Shelf life of up to 24 months
- Flame retardant (UL 94 VO) and LOI of at least 28%
- Container and cover made from flame retardant UL94-V0 material, highly resistant to shock and vibration

- Lead carbon added to negative electrodes increases power and reduces sulfation
- High potential fuel savings when used with hybrid genset applications
- Operating temperature range -40°C to +65°C (-40°F to 149°F)
- State-of-the-art automated manufacturing ensures consistency and reliability
- Advanced 3 stage terminal design to ensure leak-free operation - brass terminals provide maximum performance
- Non-halogenated thermally sealed plastic casing
- Approved as non-hazardous cargo for ground sea and air transport DOT 49CFR173.159(d), (i) and (ii)

Release date: 2024-01-29



NSB 100FT BLUE+

Technical Specifications


Dimensions (Nominal)

Height	11.3 in	Width	4.3 in
Length	15.6 in	Weight	72 lbs

Electrical

Terminal	Female M8	
Terminal torque	5.0 Nm (44 in-lbs)	
10 hr capacity to 1.80VPC @ 25°C (77°F)	100 Ah	
8 hr capacity to 1.75VPC @ 25°C (77°F)	100 Ah	
Float voltage @ 20/25°C (68/77°F)	2.28 / 2.27 VPC	
Impedance (1Khz)	5.6 m Ω @ 25°C (77°F)	
Conductance	S	
Short circuit current	2210 A	
Maximum charge current (A)	No Limit	
Operation temperature range	-40°C to +65°C	
Nominal voltage	12 V	

Technical Drawing



- Approved as non-hazardous cargo for ground, sea, and air transportation in accordance with US DOT Regulation 49 and ICAO & IATA Packing Instruction 806. Please see our SDS for complete details at www.enersys.com
- • Complies with Telcordia § SR-4228, Network Equipment Building System (NEBS M) Criteria Levels
- The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified