

NSB 60FT BLUE+



The NSB BLUE+ Battery® delivers ultra fast recharge and exceptional PSoC cycling performance.

- Exceptional PSoC cyclic performance 2050 cycles @50% DoD
- Design life 12+ years at 20°C (68°F)
- EUROBAT design life definition: Very Long Life (12+ years)
- Ultra fast recharge
- Shelf life of up to 24 months
- Lead carbon added to negative electrodes increases power and reduces sulfation

- High potential fuel savings when used with hybrid genset applications
- Operating temperature range -40°C to +65°C (-40°F to 149°F)
- State-of-the-art automated manufacturing ensures consistency and reliability
- Advanced 3 stage terminal design to ensure leak-free operation - brass terminals provide maximum performance
- High modulus Polyphenylene Oxide (PPO) plastic materials designed to withstand extended elevated operating temperatures and maintain high battery compression essential for reliable operation
- Non-halogenated thermally sealed plastic casing
- Approved as non-hazardous cargo for ground sea and air transport DOT 49CFR173.159(d), (i) and (ii)



NSB 60FT BLUE+

Nominal Technical Specifications


Dimensions

Height	263 mm	Width	108 mm
Length	287 mm	Weight	23 kg

Flectrical

Terminal	Female M8 x 1.25	
Terminal torque	8.0 Nm (71 in-lbs)	
10 hr capacity to 1.80VPC @ 25°C (77°F)	60 Ah	
8 hr capacity to 1.75VPC @ 25°C (77°F)	59 Ah	
Float voltage @ 20/25°C (68/77°F)	2.28 / 2.27 VPC	
Impedance (1Khz)	3 m Ω @ 25°C (77°F)	
Conductance	1550 S	
Short circuit current	1960 A	
Maximum charge current (A)	No Limit	
Operation temperature range	-40°C to +65°C	
Nominal voltage	12 V	

Technical Drawing



All NorthStar batteries are compliant with: Telcordia SR4228, IEC 60896; Bellcore GR-63-Core, Issue 1; British, German, and Russian telecom standards; UL approved and UN2800 certified. NorthStar is registered to ISO 9001 and ISO 14001.